



This Workhorse Is A Sprinter.



The OKI[®] MICROLINE[®] 395 and four-color ML395C printers are built to deliver trouble-free reliability — with relentless, high-volume

output, flexible paper handling, and swift printing speeds.

Each of its four print speeds is among the fastest in its class. At

610 cps, the High-Speed Draft mode blasts through spreadsheet reports in no time. The 485-cps Utility and 245-cps Near Letter Quality modes kick out drafts and memos at a rapid clip. And the 165-cps Letter Quality mode delivers crisp, clear correspondence and proposals in short order. Use the ML395/395C's optional bottom push tractor and the bottom feed's straight-through paper path for those hard-to-handle labels,

card stock, and forms with up to 5 parts. Add the top feed for single sheets and envelopes, the rear push feed for fanfold paper.

A time-saving “paper park” function lets you switch forms at the push of a button. And, for trouble-free unsupervised operation, there are optional single- or dual-bin cut sheet feeders. The ML395 even saves paper: its zero-tear function advances a printed page to the perforation and lets you tear it off cleanly and precisely. Then it positions the next page for printing automatically.

The Tank-Tough[®] printer with flexible forms handling, and lightning-fast throughput.



Getting The Job Done—With Style.

Make a lasting, professional-looking impression with the ML395/395C's four built-in, letter-quality resident fonts, eight resident bar code fonts, including USPS-certified PostNet™ — to save you money on mailings.

The ML395/395C lets you get up and running easily with all of today's popular software programs, and its Novell® compatibility makes it network-ready.

For quick attachment to a variety of systems, the printer also features parallel and serial interfaces, standard.



Add dazzle to your graphics and text with the ML395C Color printer.

With the ML395C, your graphics, charts, transparencies and text presentations will sizzle in a vibrant rainbow of colors, as well as black.

For those users who demand the ultimate sharpness in their text, an optional black film ribbon works with both the ML395 and ML395C. Use it for proposals and letters that have to look their crisp, professional best.

Rugged. Dependable. Virtually unstoppable.

The ML395/395C is all that and more. It comes with a printhead rated for 200 million characters. And the ML395 has an MTBF of 8,000 hours.

Ask your Authorized OKI Dealer to show you the fast, flexible 24-pin workhorse that's sure to be a winner in your busy office: the ML395/395C.

ML395/395C 24-PIN IMPACT PRINTERS

Technology

Printhead: 24-pin, (0.20 mm diameter)

Print Speed:

Mode	LQ	NLQ	Utility	HS Draft
Speed (in cps)	165	245	485	610

Graphics Resolution: 60 x 60 dpi (min.); 360 x 360 dpi (max.)

Feed Rate: 10 ips

Compatibility

Emulations: Epson® LQ 2550 and IBM® XL24E co-resident

Support: Novell® 4.x; MS-DOS®; Windows® 95/98

Fonts

Code Pages: Standard ASCII; Epson Character I, II, IBM I, II and All; 16 Foreign Language Sets; Line Graphics; 850/863/437

Scalable: Courier, Swiss™, Roman, Orator

Bar codes: UPC A, UPC E, Code 39, EAN 8, EAN 13, Interleaved 2 of 5, Code 128 (A, B, C), PostNet™

Interface

Co-resident: Parallel and RS232-C Serial

Memory

RAM: 64Kb

Interface Buffer: Max. 23Kb

Paper Handling

Paper Input: Multi-Part Form, Continuous Form (non-overlap type), Cut Sheet, Card Stock, Envelopes (single feed)

Number of Copies: Original plus 3

Single Sheet Thickness: 0.002" to .0049" (0.05mm to 0.12mm)

Multipart Thickness: Rear Feed .014" (0.36mm); Bottom Feed .02" (0.5mm)

Paper Weight: Single Part – 12 to 24 lb.; Card Stock – 100 lb. or less

Paper Feeding: Bottom, Top and Rear

Standard: Built-in Push Tractor (Rear Feed), Friction Feed (Top)

Options: Pull Tractor, Bottom Feed Push Tractor, Single and Dual Bin Cut Sheet Feeders

Warranty and Reliability

Limited Warranty: One year parts, labor, and printhead

MTBF: 8,000 hours (25% duty/35% page density)

Printhead Life: 200 Million characters avg. @ 25% duty cycle

Environmental

Size (WxDxH): 22.4" x 16.4" x 7.1" (57 cm x 41.7 cm x 18.0 cm)

Net Weight: 37 lb. (17 kg); UPS shippable

Noise: 58dBA LQ mode; 56dBA Quiet mode

Power Consumption: 180 VA (max.) operating; 60 VA idle

Electrical: 120V, 220/240V (+10%, -15%)

Frequency: 50/60 Hz (±2%)

Operating Temperature: 41°F to 104°F (5°C to 40°C) @ 20% to 80% relative humidity

Ordering Information (Part Number)

Printer:

ML395 – 120V	62410501
ML395 – 220/240V	62410502
ML395C – 120V	62410601
ML395C – 220/240V	62410602

Accessories:

Single Bin Cut Sheet Feeder	70010601
Dual Bin Cut Sheet Feeder	70010701
Pull Tractor Kit (with acoustic cover)	70011701
Bottom Feed Push Tractor Kit	70021601
OkilAN® 10 Base-T Ethernet	
External Print Server	70034401

Ribbons:

Black Cartridge	52103601
Color Cartridge	52103701
Black Film Cartridge	52103801

All specifications subject to change without notice.

© 1999 Okidata, a Division of Okidata America, Inc. OKI Reg. T.M., M.D., M.R., Oki Electric Industry Co., Ltd. MICROLINE, OkilAN Reg. T.M., People to People Technology and design T.M., Oki Electric Industry Co., Ltd. 7-Day/24-Hour logo T.M., Okidata America, Inc. Epson Reg. T.M., Seiko Epson Corp. IBM, Reg. T.M., International Business Machines Corp. Novell, YES Tested & Approved logo Reg. T.M., Novell, Inc. MS-DOS, Windows Reg. T.M., Microsoft Corp. PostNet, T.M., USPS. Swiss, T.M., Bitstream, Inc. Energy Star Reg. T.M., U.S. EPA.

Printed in USA.

MS9397/0399

To Contact Okidata:

In USA:
2000 Bishops Gate Blvd.
Mount Laurel, NJ 08054-4620
Tel: 800.OKIDATA (800.654.3282)
Tel: 609.222.5320
Fax: 609.222.5320

Web Site: www.okidata.com

In Canada:
2735 Matheson Blvd. East
Mississauga, Ontario L4W 4M8
Tel: 905.238.4250
Tel: 905.238.4421
Fax: 905.238.4421

Okidata División Internacional:
2000 Bishops Gate Blvd.
Mount Laurel, NJ 08054-4620
Tel: 609.231.0002
Tel: 609.222.5071
Fax: 609.222.5071



Novell.

